

(12) UK Patent Application (19) GB (11) 2 315 954 (13) A

(43) Date of A Publication 11.02.1998

(21) Application No 9716232.5

(22) Date of Filing 31.07.1997

(30) Priority Data

(31) 08203625 (32) 01.08.1996 (33) JP

(71) Applicant(s)

NEC Corporation

(Incorporated in Japan)

7-1 Shiba 5-Chome, Minato-Ku, Tokyo 108-01, Japan

(72) Inventor(s)

Keiichirou Kumagai

(74) Agent and/or Address for Service

Reddie & Grose

16 Theobalds Road, LONDON, WC1X 8PL,
United Kingdom

(51) INT CL⁶

H04Q 7/32, H04M 1/274 1/66

(52) UK CL (Edition P)

H4K KBHF KBNJ

(56) Documents Cited

GB 2305073 A GB 2293946 A EP 0730387 A2

EP 0310876 A2 EP 0194387 A2 US 5541988 A

US 5222127 A

JAPIO Abstract Accession No.04111368 & JP
050103068 A

(58) Field of Search

UK CL (Edition O) H4K KBHF KBNJ, H4L LECC


INT CL⁶ H04M 1/274 1/66, H04Q 7/32

ONLINE:WPI

(54) Portable telephone having personalised data storage and management for plurality of users

(57) A portable or cordless telephone handset has a storage section 10 for managing personal numbers and data for a plurality of individual users, whereby the users can use the device in a mode set according to their individual requirements. For each user the communication unit stores identification information such as a password, fingerprint or voiceprint and corresponding personal data which can include telephone settings, a personal number (PSID) and a telephone directory (figure 2). The portable telephone comprises a central control unit 6 that controls a radio section 2, a voice processing section 3, an operation section 7, a display section 8 and a data processing section 9. The central control unit 6 includes a user retrieving section 11. By inputting identification information from the operation section 7, the device is switched to personal mode. Accordingly, a personal number (PSID) for each user can be transmitted or received and data can be managed on a personal basis. Applications include managing a device used for both business and private purposes and managing individual call tariffs.

FIG. 1



GB 2 315 954 A

FIG. 1




FIG.2

PERSONAL DATA 1		PERSONAL DATA 2		PERSONAL DATA 3	
DATA OF TELEPHONE NUMBER, INITIAL SETTING etc.	PSID 1	DATA OF TELEPHONE NUMBER, INITIAL SETTING etc.	PSID 2	DATA OF TELEPHONE NUMBER, INITIAL SETTING etc.	PSID 3

FIG. 3




FIG. 4




FIG. 5




FIG.6




FIG. 7





FIG. 8

PRIOR ART



PORTABLE COMMUNICATION DEVICE

BACKGROUND OF THE INVENTION

The present invention relates to a portable communication device.

5 Referring first to Fig. 8 of the drawings, there is shown a conventional portable communication device, typically a portable (cordless) telephone set, which comprises an antenna section 21 for transmitting/receiving a radio wave, a radio section 22 for transmitting/receiving a radio signal, a
10 voice processing section 23 for processing a voice signal, a microphone section 24 for voice input, a speaker section 25 for voice output, a central control unit 26 for controlling the entire portable communication device, an operation section 27 having buttons, switches, and so on, arranged so
15 as to input an operation signal from a user, a display section 28 for performing displaying, and a memory section 29 for storing data.

The operation of the conventional portable communication device constructed in the above-noted manner will now be
20 described. When intending to input data regarding a telephone number, an address book or the like, or an initial setting regarding a function at the time of starting, to

the memory section 29, a user inputs data to be stored to the memory section 29 from the operation section 27. The data input from the operation section 27 is displayed on the display section 28. After having confirmed the display, the user presses the button for storing the data in the memory section 29 from the operation section 27 and then the central control unit 26 causes the memory section 29 to store the input data. When data is to be added to the memory section 29, data addition can be continued by repeating the above-noted operation until there are no more vacant areas in the memory section 29.

When the data stored in the memory section 29 is to be read or changed, the data to be read is specified, the central control unit 26 reads the data from the memory section 29, the read data is displayed on the display section 28 and then this data is changed by the operation section 27 while confirming the display on the display section 28. The user can confirm and change the data stored at the time of initial setting by performing the same operation. The data stored in the memory section 29 is backed up so as to be prevented from being erased even when power is turned OFF. By turning ON power again for the portable communication device, the mode is changed to the initial setting of the last input data.

Referring to JP-A-21884/1994, there is disclosed a radio

communication device comprising a master machine connected
to a cable channel and a slave machine communicating with
the master machine by radio. In this case, when the
slave machine is used by a plurality of individuals,
5 memory information including a telephone number, initial
setting, and so on, input for each user, is divided into
blocks and stored and managed en block in the storage
memory of the master machine, and by transferring this
information from the master machine to the slave machine
10 so as to change the content of the memory information of
the slave machine, memory information including a
telephone number, initial setting, and so on, can be set
for the slave machine.

However, there were problems inherent in such a known
15 portable communication device. One problem is that when
one device is used by a plurality of individuals, the base
station cannot identify the user when the device is used
by the plurality of individuals. Consequently, a
telephone directory or a call tariff cannot be managed on
20 a personal basis.

Another problem is that memory information including
a telephone number, initial setting, and so on, for each

user must be transferred from the master machine to the slave machine, and this operation is troublesome.

SUMMARY OF THE INVENTION

The invention in its various aspects is defined in the independent claims below, to which reference should now be made. Advantageous features are set forth in the appendant claims.

A preferred embodiment of the present invention is described in more detail below with reference to the drawings, and takes the form of a portable communication device, which comprises storing means for storing data regarding a plurality of users and identification information regarding the said plurality of users in a corresponding manner for each user, and managing means for managing data for each user based on the identification information. The portable communication device comprises a storage section for storing data regarding the plurality of individuals, wherein data for each user can be managed on a personal basis.

Furthermore, if a telephone number or personal identification for each user (referred to as PSID, hereinafter) is stored in the storage section, a PSID for

each user can be selected from the storage section and transmitted or received. Accordingly, telephone numbers, call tariffs, and so on, can be managed for each user. Also, the same effect as that when one individual has a plurality of portable communication devices is provided and thus one device can be separately used for private and business purposes. The plurality of users can call or receive calls using one communication device.

For identification information, the fingerprint, the voiceprint, and so on, of a user, can be used in addition to a password.

BRIEF DESCRIPTION OF THE DRAWINGS

This and other features and advantages of the present invention will become more apparent upon a reading of the following detailed description and drawings, in which:

Fig. 1 is a block diagram illustrating a portable telephone set embodying the present invention;

Fig. 2 is a view illustrating the personal data storage section 10 of the telephone set of Fig. 1;

Fig. 3 is a flowchart illustrating the operation of the portable telephone set of Fig. 1;

Fig. 4 is a flowchart illustrating another operation of the portable telephone set of Fig. 1;

Fig. 5 is a flowchart illustrating yet another operation of the portable telephone set of Fig. 1;

5 Fig. 6 is a block diagram illustrating another portable telephone set embodying the present invention;

Fig. 7 is a block diagram illustrating a further telephone set embodying the present invention; and

10 Fig. 8 is a block diagram illustrating a conventional portable communication device.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The preferred embodiments of the present invention will be described below with reference to the accompanying drawings. In the embodiments, a portable (cordless)
15 telephone handset which is typical of a portable communication device will be taken as an example.

First, the circuitry of the portable telephone set of the first embodiment of the present invention will be described by referring to Fig. 1.

A signal transmitted from a base station is received by an antenna section 1, passed through a radio section 2 and a voice processing section 3 and then outputted as a voice signal from a speaker section 5.

5 A voice signal from a microphone section 4 is passed through the voice processing section 3, the radio section 2 and the antenna section 1, transmitted to the base station and then communication is carried out. A central control unit 6 controls the radio section 2, the voice
10 processing section 3, an operation section 7, a display section 8 and a data processing section 9. The central control unit 6 includes a user retrieving section 11.

Next, the operation of the portable communication device (portable telephone set) of Fig. 1 will be
15 described.

First, registration of a user is performed by using a password. This password may be numerals such as 01234 or characters such as ABCD. The password corresponds to data regarding a user stored in a personal data storage section
20 10. The data regarding each user is divided into blocks and stored in the personal data storage section 10. Accordingly, by setting a password for each user, the data regarding each user can be managed on a personal basis. The data regarding each user means data regarding a
25 telephone number, an address book or the like or initial

setting regarding a function at the time of starting.

5 A personal number (PSID) for each user is also divided
into blocks and registered beforehand in the personal data
storage section 10. By setting a password corresponding to
each PSID, use by a plurality of individuals and
management on a personal basis can be allowed. The PSID
means a telephone number that the portable telephone set
has. For example, characters may be placed after a normal
telephone number, such as 101 (12) 3455 * 1 and 101 (12)
10 3455 * 2, and alternatively a plurality of telephone
numbers completely different from one another may be
given to one telephone set.

Referring to Fig. 2, there is shown an example of
storing in the personal data storage section 10. Data
15 shown is based on the case that three individuals use one
portable telephone set. Each personal data is stored in
each storage area obtained by division into blocks.

Next, the operation of inputting data to the personal
data storage section 10 performed by a user will be
20 described.

A password is input from the operation section 7. The
user retrieving section 11 collates this password. If
coincidence for the password is discovered, then a mode is
switched to setting for each user (personal mode). Then,
25 data to be stored in the personal data storage section 10

is input from the operation section 7. The data input from the operation section 7 is then displayed on the display section 8. After having confirmed the display, the user presses a button for storing the data in the personal data storage section 10 from the operation section 7, and thereby the central control unit 6 stores the data in the personal data storage section 10 via the data processing section 9.

When data is to be added to the personal data storage section 10, data addition can be continued by repeating the above-noted operation until no more vacant areas exist in the personal data storage section 10.

When the data stored in the personal data storage section 10 is to be read or changed, similarly to the above-noted operation, a password is first input from the operation section 7 and the operation is switched to the personal mode. Then, the data to be read is specified by the operation section 7, and thereby the central control unit 6 reads the personal data storage section 10 via the data processing section 9 and then displays the data on the display section 8. The data is changed by the operation section 7 while confirming the display on the display section 8. The user can also confirm and change the stored data regarding initial setting or the like by performing a similar operation. The data stored in the

personal data storage section 10 is backed up so as to be prevented from being erased even when power is turned OFF. A condition is returned to initial setting for the last input data by turning ON power again for the portable communication device.

Referring to Fig. 3, there is shown a flowchart illustrating an operation procedure for making a switch to the personal mode. First, in step S1, a password is input from the operation section. In step S2, retrieving is performed for the input password. In step S3, determination is made as to whether the password has been retrieved or not. If the retrieval of the password is determined in step S3, the process proceeds to step S4, where a switch is made to the personal mode for each user and then the portable communication device can be used by using the data stored for each user.

Next, making calling by the portable communication device of the present embodiment will be described by referring to the flowchart shown in Fig. 4.

For making calling, in step S10, first a switch must be made to the personal mode. The operation of making a switch to the personal mode was made above by referring to Fig. 3 and thus its description will be omitted.

After the personal mode has been set, in step S11, the PSID for each user is read from the personal data storage

section 10 via the data processing section 9.

5 If calling is to be made to the telephone number whose data has been registered in step S12, the telephone number to be addressed to is read from the personal data storage section 10 by pressing the button of the operation section 7 in step S13. By confirming the telephone number displayed on the display section 8, the calling button of the operation section 7 is pressed and then calling is made in step S14. Then, the PSID of the user and the
10 telephone number to be addressed to are transmitted from the antenna section 1 through the radio section 2.

In this case, the PSID to be transmitted must be registered beforehand in the base station. Since the transmitted PSID can also be read from the base station in
15 this way, a call tariff can be managed for each user.

For calling made to an address whose data has not been registered in step S12, its telephone number is input and then transmitted in step S15. In this case, the PSID to be transmitted is also registered beforehand in the base
20 station. Since the transmitted PSID can also be read from the base station, a call tariff can be managed for each user.

Next, the case of an incoming call will be described by referring to a flowchart shown in Fig. 5. For an incoming
25 call, the operation is also performed based on the

personal mode in step 20. Thus, description of the operation until making a switch to the personal mode will be omitted.

5 First, user PSID corresponding to password is read in step S21.

10 A PSID transmitted from the base station is received by the antenna section 1, passed through the radio section 2 in step S22 and confirmation is made as to whether this PSID coincides with a currently used PSID for each user or not in the user retrieving section 12 in step S23. If coincidence is discovered in step S24, communication is allowed in step S25. If no coincidence is discovered between the PSID transmitted from the base station and the currently used PSID for each user, communication is not
15 allowed in step S26. Accordingly, even when one portable communication device is used by a plurality of individuals, no calls other than that from the user currently using the device come in.

20 Another embodiment of the present invention will be described.

As means for identifying a user, in addition to a password, a fingerprint or a voiceprint can be used. In such a case, instead of the operation section 7 for inputting a password, a circuit for registering a
25 fingerprint or a voiceprint and performing retrieval

during use may be provided. Accordingly, troublesome work of inputting a password can be eliminated.

Referring to Fig. 6, there is shown in block a portable telephone set, which includes a fingerprint sensing section 12.

The fingerprint sensing section 12 shown can read the fingerprint of a user. The user inputs his/her own fingerprint information instead of a password by the fingerprint sensing section 12 and stores this information in the personal data storage section 10 beforehand. In this way, instead of collating of the password, by performing collation for the fingerprint, personal data can be managed.

Referring to Fig. 7, there is shown in block a portable telephone set, which includes a voiceprint sensing section 13.

The voiceprint sensing section 13 shown can read the voiceprint of a user. The user inputs his/her own voiceprint information instead of a password by the voiceprint sensing section 13 and stores this information in the personal data storage section 10 beforehand. In this way, instead of collating of the password, by performing collation for the voiceprint, personal data can be managed.

The above-described portable communication device can be

used by a plurality of individuals. In addition, the device is used by one individual separately for both business and private purposes.

5 As described above, the portable communication device illustrated includes the storage section for individually storing data regarding a plurality of individuals, data regarding each user can be managed by using a password on a personal basis and a PSID for each user can be selected from the storage section, transmitted and received. Accordingly, a telephone number, a call
10 tariff, and so on, can be managed for each user. In other words, even when one portable communication device is used by a plurality of individuals, the user can use the device feeling that the device is his/her own.

15 Furthermore, if one portable communication device is used by one individual, an effect similar to that obtained when a plurality of devices are owned by one individual can be provided and one device can be used separately for private and business purposes. -

CLAIMS

1 A portable communication device comprising:

storing means for storing data regarding a plurality of
users and identification information regarding said
5 plurality of users in a corresponding manner for
each user; and

managing means for managing data for each user based on
said identification information.

2 The portable communication device of claim 1, wherein
10 said data for each user comprises a telephone number of said user.

3 The portable communication device of claim 1, wherein
said user for each user comprises a personal number.

4 The portable communication device of claim 1, wherein
said storing means comprises means for storing a password
15 as identification information for each user and said
managing means manages corresponding data for said user
based on said password.

5 The portable communication device of claim 1, wherein
said storing means comprises means for storing fingerprint
20 information as said identification information for each
user and said managing means comprises collating means for
collating said fingerprint information for each user with
a specified fingerprint and means for managing
corresponding data for said user based on a result of
25 collation between said fingerprint information and said

specified fingerprint information performed by said collating means.

5 6 The portable communication device of claim 1, wherein said storing means comprises means for storing voiceprint information as said identification information for each user and said managing means comprises collating means for collating said voiceprint information for each user with a specified voiceprint and means for managing corresponding data for said user based on a result of collation between
10 said voiceprint information and said specified voiceprint performed by said collating means.

7 A portable communication device comprising:

storing means for storing personal data
regarding a plurality of users and passwords
15 for said plurality of users in a corresponding manner for each user;
password inputting means for inputting a password for each user;
collating means for collating a password input
20 by said password inputting means with identification information stored in said storing means;
means for reading and displaying personal data for a user corresponding to said input
25 password after coincidence is discovered

between said password and said identification
information by said collating means; and
means for renewing personal data for each user
corresponding to said input password after
coincidence is discovered between said
password and said identification information
by said collating means.

5

10

15

8 The portable communication device of claim 7, wherein
said storing means comprises means for storing fingerprint
information for each user instead of a password,
fingerprint information inputting means for inputting
information regarding a fingerprint is provided instead of
said password inputting means and said collating means
includes means for collating fingerprint information input
by said fingerprint inputting means with said fingerprint
information for each user.

20

25

9 The portable communication device of claim 7, wherein
said storing means stores voiceprint information for each
user instead of a password, voiceprint information
inputting means is for inputting information regarding a
voiceprint is provided instead of said password inputting
means and said collating means includes means for
collating voiceprint information input by said voiceprint
information inputting means with said voiceprint
information for each user.

10 A portable communication device comprising:

storing means for storing telephone numbers for
a plurality of users and identification
information regarding said plurality of users
in a corresponding manner for each user;

identification information inputting means for
inputting identification information for each
user;

collating means for collating identification
information input by said identification
information inputting means with
identification information stored in said
storing means;

reading means for reading a telephone number for
each user corresponding to said
identification information collated by said
collating means from said storing means; and
transmitting means for transmitting said read
telephone number as a telephone number of a
caller side.

11 The portable communication device of claim 10,
wherein said storing means comprises means for storing a
password as identification information for each user,
a password is input by said identification information
inputting means and collation is performed for said input

password by said collating means.

12 The portable communication device of claim 10,
wherein said storing means comprises means for storing
fingerprint information for each user as said

5 identification information for each user, fingerprint
information is input by said identification information
inputting means and collation is performed for said input
fingerprint information by said collating means.

13 The portable communication device of claim 10,
10 wherein said storing means comprises means for storing
voiceprint information for each user as said
identification information for each user, voiceprint
information is input by said identification information
inputting means and collation is performed for said input
15 voiceprint information by said collating means.

14 A portable communication device comprising:

storing means for storing telephone numbers for
a plurality of users and identification
information regarding said plurality of users
20 in a corresponding manner for each user;
identification information inputting means for
inputting identification information for each
user;
first collating means for collating
25 identification information input by said

identification information inputting means
with identification information stored in
said storing means;

5 reading means for reading a telephone number of
a user corresponding to said identification
information collated by said collating means
from said storing means;

10 second collating means for collating said read
telephone number with a telephone number of
an incoming call; and

connecting means for connecting said incoming
call so as to enable communication when
coincidence is discovered between said
telephone numbers by said second collating
15 means.

15 15 The portable communication device of claim 14,
wherein said storing means comprises means for storing a
password as identification information for each user,
a password is input by said identification information
20 inputting means and collation is performed for said input
password by said collating means.

25 16 The portable communication device of claim 14,
wherein said storing means comprises means for storing
fingerprint information for each user as said
identification information for each user, fingerprint

information is input by said identification information
inputting means and collation is performed for said input
fingerprint information by said collating means.

17 The portable communication device of claim 14,
5 wherein said storing means comprises means for storing
voiceprint information for each user as said
identification information for each user, voiceprint
information is input by said identification information
inputting means and collation is performed for said input
10 voiceprint information by said collating means.

18 A portable communication device, substantially as
herein described with reference to Figs. 1 to 7 of the
drawings.



Application No: GB 9716232.5
Claims searched: 1-18

Examiner: Anita Keogh
Date of search: 1 October 1997

Patents Act 1977
Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:

UK Cl (Ed.O): H4K (KBNJ, KBHF), H4L (LECC)

Int Cl (Ed.6): H04M (1/274, 1/66), H04Q (7/32)

Other: Online: WPI

Documents considered to be relevant:

Category	Identity of document and relevant passage		Relevant to claims
X,P	GB 2305073 A	(MOTOROLA) see whole document and particularly page 4, lines 6-32 and page 5 lines 29-33	1-4 at least
X	GB 2293946 A	(MOTOROLA) see whole document	1 at least
X,P	EP 0730387 A2	(IBM) see whole document	1-3 at least
X	EP 0310876 A2	(MOTOROLA) see particularly column 3, lines 8-39 and column 5, lines 17-41	1-3 at least
X	EP 0194387 A2	(TOMY KOGYO) see abstract and particularly page 3, lines 10-25	1-3,6 at least
X	US 5541988	(DRAGANOFF) see abstract, column 1 lines 59-67 and column 2 line 51 to column 3 line 6	1,4,7 at least
X	US 5222127	(FUKUI) see particularly column 2, lines 12-44	1,2 at least
X	JAPIO Abstract Accession No. 04111368 & JP 050103068 A (FUJITSU) 23.04.93		1,2,3,5,10 at least

X Document indicating lack of novelty or inventive step
Y Document indicating lack of inventive step if combined with one or more other documents of same category.
& Member of the same patent family

A Document indicating technological background and/or state of the art.
P Document published on or after the declared priority date but before the filing date of this invention.
E Patent document published on or after, but with priority date earlier than, the filing date of this application.